



**Product Number:** 54604

**Order Abbreviation:** HPL 550/77/X (UCF)

**General Description:** 550 watt, tungsten halogen, HPL series, long life

#### Product Information

|                                   |                                 |
|-----------------------------------|---------------------------------|
| Abbrev. With Packaging Info.      | HPL55077X (UCF) 77V 12/CS 1/SKU |
| Application                       | Stage & Studio                  |
| Average Rated Life (hr)           | 2000                            |
| Base                              | Medium Bip in with Heat Sink    |
| Bulb                              | T6                              |
| Class                             | C (gas)                         |
| Color Rendering Index (CRI)       | 100                             |
| Color Temperature (K)             | 3065                            |
| Diameter d (in)                   | 0.748                           |
| Diameter d (mm)                   | 19.00                           |
| Distance a (in)                   | 2.352                           |
| Distance a (mm)                   | 60.3                            |
| Family Brand Name                 | HPL                             |
| Filament                          | 4-C8                            |
| Lamp Finish                       | Clear                           |
| Length l (in)                     | 4.1                             |
| Length l (mm)                     | 104                             |
| Length l max. (in)                | 4.1                             |
| Length l max. (mm)                | 104                             |
| Light Center Length - LCL (in)    | 2.352                           |
| Light Center Length - LCL (mm)    | 60.3                            |
| Luminous Flux (lm)                | 12160                           |
| Maximum Overall Length - MOL (in) | 4.1                             |
| Maximum Overall Length - MOL (mm) | 104                             |
| Nominal Voltage (V)               | 77.00                           |
| Nominal Wattage (W)               | 550.00                          |
| Operating Position                | Any                             |
| Reflector Coating                 | 19.00                           |
| Type of Current                   | AC                              |

**Footnotes**

- High-performance HPL halogen lamps are manufactured under license from ETC, Inc.